

MADE IN INDIA

SU=maK[®]
SOLAR

eco
Advance
PURE SINE WAVE UPS
2000/24V



www.sumaksolar.com | export@sumaksolar.com | info@sumaksolar.com

Technical Specification

MODEL	2000
Volt	24V

VOLTAGE LIMITS NARROW WINDOW (UPS MODE)

Mains A.C. Low Cut	185 $\pm$ 10V
Mains A.C. Low Cut Recovery	190 $\pm$ 10V
Mains A.C. High Cut	265 $\pm$ 10V
Mains A.C. High Cut Recovery	260 $\pm$ 10V

VOLTAGE LIMITS WIDE WINDOW (W-UPS MODE)

Mains A.C. Low Cut	85 $\pm$ 10V
Mains A.C. Low Cut Recovery	90 $\pm$ 10V
Mains A.C. High Cut	290 $\pm$ 10V
Mains A.C. High Cut Recovery	275 $\pm$ 10V

OUTPUT PARAMETER

Mains Output	Same as Input (45Hz-55Hz)
Output Frequency	50.0 Hz. $\pm$ 0.1 Hz
Output Voltage with Full Load	200V/220V $\pm$ 15V
Waveform	Sine Wave
Overload	Above 100%
Short Circuit Protection	>200% Load (Few msec)

BATTERY CHARGING

FLC based SMPS charging with soft start over full range of mains	85V to 290V $\pm$ 10V
Battery type	SMF/TUBULAR/ Flooded LEAD ACID
Charging Current	5A /10A / 15A $\pm$ 2.0Amp
Recommended Battery Capacity	25AH-200AH
Number of Batteries	2

TECHNOLOGY

Digital Signal Processor based state-of-the-art technology using MOSFETs
--

ENVIRONMENT

Storage Temp.	0-55°C
Operating Temp.	0-50°C
Humidity	90% Non-condensing
Dimension (W X D X H) in mm $\pm$ 5mm	407 x 304 x 172
Weight Net (Kg) $\pm$ 0.5Kg	14.8 Kg

Note : Specifications are subject to change without any prior notice.



Marketed By.: Su-mak Power Systems Pvt. Ltd.

Plot no.49, phase 2, 8th cross road, G T Road, Nellore -524004,
Andhra Pradesh, India

web: www.sumaksolar.com | export@sumaksolar.com