

CLASSIC

SERIES



TECHNICAL SPECIFICATIONS

Suction Lift : Super Suction Up to 8m (at mean sea level)
Motor Rating : 0.18 - 1.10 kW (0.25 - 1.50 hp)
Head (m) : 5 - 45 **Pipe Size (mm)** : 15 X 15 & 25 X 25
Capacity (lph) : up to 3400 **Temperature** : Ambient (40 °C)

MODEL	MOTOR RATING		PIPE SIZE IN MM SUC. X DEL.	TOTAL HEAD IN METERS													
	kW	HP		05	08	12	16	20	24	28	30	32	36	40	45	DISCHARGE IN LPH	
CLASSIC 25	0.18	0.25	15 X 15	1300	1225	1000	775	475									
CLASSIC 50	0.37	0.50	15 X 15	1700	1600	1475	1275	1050	800	350							
CLASSIC 50 X	0.37	0.50	25 X 25	2000	1800	1620	1420	1225	975	650	400						
CLASSIC 75	0.55	0.75	25 X 25	2100	2000	1800	1600	1425	1250	1000	800	475					
CLASSIC 100	0.75	1.00	25 X 25	2350	2250	2100	1925	1725	1500	1250	1100	975	700	300			
CLASSIC 100 X	0.75	1.00	25 X 25	2100	1960	1780	1600	1410	1210	1000	860	725					
CLASSIC 150X	1.10	1.50	25 X 25	3400	3100	2850	2700	2500	2350	2150	2055	1950	1700	1375	750		

RYNO

SERIES



TECHNICAL SPECIFICATIONS

Suction Lift : Super Suction Up to 8m (at mean sea level)
Motor Rating : 0.37 kW (0.50 hp)
Head (m) : 5 - 35 **Pipe Size (mm)** : 25 X 25
Capacity (lph) : up to 2200 **Temperature** : Ambient (40° C)

MODEL	MOTOR RATING		PIPE SIZE IN MM SUC. X DEL.	TOTAL HEAD IN METERS							
	kW	HP		05	10	15	20	24	28	32	35
RYNO 50-35	0.37	0.50	25 X 25	2100	1700	1350	975	700	425	150	
RYNO 50-40	0.37	0.50	25 X 25	2200	1800	1500	1200	950	700	475	300



SILVER ENGINEERING COMPANY

PERFORMANCE CHART FOR SELF PRIMING MONO BLOCK PUMPSET

MODELS	MOTOR RATING		PIPE SIZE IN MM	TOTAL HEAD IN METRES								
				5	10	15	20	24	28	32	35	40
	KW	HP	SUC x DEL	DISCHARGE IN LPH								
RYNO 50-35	0.37	0.50	25 X 25	2100	1700	1350	975	700	425	150	0	
RYNO 50-40	0.37	0.50	25 X 25	2200	1800	1500	1200	950	700	475	300	0

